

**NEW PATENT APPLICATION COVER PAGE**

**TITLE: A CATALYST COMPOSITION AND METHODS FOR ITS  
PREPARATION AND USE IN A POLYMERIZATION PROCESS**

This nonprovisional application claims priority from U.S. provisional application number 60/256,744, filed December 19, 2000, the disclosure of which is incorporated herein in its entirety by reference.

**ATTY. DOCKET: 2000U055.US**

**INVENTORS:**

**Agapios Kyriacos Agapiou  
19911 17<sup>th</sup> Green Court  
Humble, Texas 77346  
Citizenship: United States of America**

**Chi-I Kuo  
19410 Cluster Oaks Drive  
Humble, Texas 77346  
Citizenship: United States of America**

**David M. Glowczwski  
7407 Lone Oak  
Baytown, Texas 77521  
Citizenship: United States of America**

**Steven K. Ackerman  
303 Chandler  
Baytown, Texas 77521  
Citizenship: United States of America**

**CORRESPONDENCE ADDRESS:**

**Osborne K. McKinney  
Lisa Kimes Jones  
Darrell Warner  
Univation Technologies, LLC  
5555 San Felipe, Suite 1950  
Houston, TX 77056**

**A CATALYST COMPOSITION AND METHODS FOR ITS PREPARATION  
AND USE IN A POLYMERIZATION PROCESS**

**CROSS-REFERENCE TO RELATED APPLICATION**

5 [0001] This nonprovisional application claims priority from U.S. provisional application number 60/256,744, filed December 19, 2000, the disclosure of which is incorporated herein in its entirety by reference.

**FIELD OF THE INVENTION**

10 [0002] The present invention relates to a catalyst composition, a method for preparing the catalyst composition and its use in a process for polymerizing olefins. In particular, the invention is directed to a method for preparing a catalyst composition comprising or made from a polymerization catalyst and <sup>1e.g.</sup> at one gelling agent or organogelator.

**BACKGROUND OF THE INVENTION**

15 [0003] Advances in polymerization and catalysis have resulted in the capability to produce many new polymers having improved physical and chemical properties useful in a wide variety of superior products and applications. With the development of new catalysts the choice of polymerization-type (solution, slurry, high pressure or gas phase) for producing a particular polymer has been greatly expanded. Also, advances in polymerization technology have provided more efficient, highly productive and economically enhanced processes. Especially illustrative of these advances is the development of technology utilizing bulky ligand metallocene catalyst systems.

20  
25 Regardless of these technological advances in the polyolefin industry, common problems, as well as new challenges associated with process operability still exist. For example, the tendency for a gas phase or slurry phase process to foul, sheet and/or generate static remains a challenge.

30 [0004] In known continuous gas phase and slurry processes, fouling and sheeting on the walls of the reactor, which act as a heat transfer surface, can result in many operability problems. For example, poor heat transfer during polymerization can result from polymer particles adhering to the walls of the reactor and continuing to polymerize on the walls, thereby leading to premature reactor shutdowns. Also, depending on the reactor conditions, some of the polymer may dissolve in the reactor diluent and redeposit, 35 for example, on the surfaces of metal heat exchangers and again contributing to poor heat transfer and cooling.

**[0005]** Further, fouling, sheeting and/or static generation in a continuous gas phase or slurry process can lead to the ineffective operation of various reactor systems. For example, premature shutdowns can occur when the cooling system of the recycle system, the temperature probes utilized for process control and/or the distributor plates are affected by fouling, sheeting and/or static generation.

**[0006]** Various process operability problems and solutions have been addressed in the art. For example, U.S. Patent Nos. 4,792,592, 4,803,251, 4,855,370 and 5,391,657 all discuss techniques for reducing static generation in a polymerization process by introducing to the process for example, water, alcohols, ketones, and/or inorganic chemical additives; PCT publication WO 97/14721 published April 24, 1997 discusses the suppression of fines that can cause sheeting by adding an inert hydrocarbon to the reactor; U.S. Patent No. 5,627,243 discusses a new type of distributor plate for use in fluidized bed gas phase reactors; PCT publication WO 96/08520 discusses avoiding the introduction of a scavenger into the reactor; U.S. Patent No. 5,461,123 discusses using sound waves to reduce sheeting; U.S. Patent No. 5,066,736 and EP-A1 0 549 252 discuss the introduction of an activity retarder to the reactor to reduce agglomerates; U.S. Patent No. 5,610,244 relates to feeding make-up monomer directly into the reactor above the bed to avoid fouling and improve polymer quality; U.S. Patent No. 5,126,414 discusses including an oligomer removal system for reducing distributor plate fouling and providing for polymers free of gels; EP-A1 0 453 116 published October 23, 1991 discusses the introduction of antistatic agents to the reactor for reducing the amount of sheets and agglomerates; U.S. Patent No. 4,012,574 discusses adding a surface-active compound, a perfluorocarbon group, to the reactor to reduce fouling; U.S. Patent 5,026,795 discusses the addition of an antistatic agent with a liquid carrier to the polymerization zone in the reactor; U.S. Patent No. 5,410,002 discusses using a conventional Ziegler-Natta titanium/magnesium supported catalyst system where a selection of antistatic agents are added directly to the reactor to reduce fouling; U.S. Patent Nos. 5,034,480 and 5,034,481 discuss a reaction product of a conventional Ziegler-Natta titanium catalyst with an antistat to produce ultrahigh molecular weight ethylene polymers; U.S. Patent No. 3,082,198 discusses introducing an amount of a carboxylic acid dependent on the quantity of water in a process for polymerizing ethylene using a titanium/aluminum organometallic catalysts in a hydrocarbon liquid medium; and U.S. Patent No. 3,919,185 describes a slurry process using a nonpolar hydrocarbon diluent using a conventional Ziegler-Natta-type or Phillips-type catalyst and a polyvalent metal salt of an organic acid having a molecular weight of at least 300.

**[0007]** There are various other known methods for improving operability including coating the polymerization equipment, for example, treating the walls of a

reactor using chromium compounds as described in U.S. Patent Nos. 4,532,311 and 4,876,320; injecting various agents into the process, for example PCT Publication WO 97/46599 published December 11, 1997 discusses feeding into a lean zone in a polymerization reactor an unsupported, soluble metallocene catalyst system and injecting antifoulants or antistatic agents into the reactor; controlling the polymerization rate, particularly on start-up; and reconfiguring the reactor design.

**[0008]** Others in the art to improve process operability have discussed modifying the catalyst system by preparing the catalyst system in different ways. For example, methods in the art include combining the catalyst system components in a particular order; manipulating the ratio of the various catalyst system components; varying the contact time and/or temperature when combining the components of a catalyst system; or simply adding various compounds to the catalyst system. These techniques or combinations thereof are discussed in the literature. Especially illustrative in the art is the preparation procedures and methods for producing bulky ligand metallocene catalyst systems, more particularly supported bulky ligand metallocene catalyst systems with reduced tendencies for fouling and better operability. Examples of these include: WO 96/11961 published April 26, 1996 discusses as a component of a supported catalyst system an antistatic agent for reducing fouling and sheeting in a gas, slurry or liquid pool polymerization process; U.S. Patent No. 5,283,278 is directed towards the prepolymerization of a metallocene catalyst or a conventional Ziegler-Natta catalyst in the presence of an antistatic agent; U.S. Patent No. 5,332,706 and 5,473,028 have resorted to a particular technique for forming a catalyst by incipient impregnation; U.S. Patent Nos. 5,427,991 and 5,643,847 describe the chemical bonding of non-coordinating anionic activators to supports; U.S. Patent No. 5,492,975 discusses polymer bound metallocene catalyst systems; U.S Patent No. 5,661,095 discusses supporting a metallocene catalyst on a copolymer of an olefin and an unsaturated silane; PCT publication WO 97/06186 published February 20, 1997 teaches removing inorganic and organic impurities after formation of the metallocene catalyst itself; PCT publication WO 97/15602 published May 1, 1997 discusses readily supportable metal complexes; PCT publication WO 97/27224 published July 31, 1997 relates to forming a supported transition metal compound in the presence of an unsaturated organic compound having at least one terminal double bond; and EP-A2-811 638 discusses using a metallocene catalyst and an activating cocatalyst in a polymerization process in the presence of a nitrogen containing antistatic agent.

**[0009]** While all these possible solutions might reduce the level of fouling or sheeting somewhat, some are expensive to employ and/or may not reduce fouling and

sheeting to a level sufficient to successfully operate a continuous process, particularly a commercial or large-scale process.

**[0010]** Applicants discovered that using a carboxylate metal salt in conjunction with a supported catalyst system, preferably a bulky ligand metallocene catalyst system, more preferably a supported bulky ligand metallocene catalyst system, substantially improves process operability. See for example U.S. Patent Application Serial No.: 09/397,409, filed September 16, 1999 and U.S. Patent Application Serial No.: 09/397,410, filed September 16, 1999, which are both herein fully incorporated by reference.

**[0011]** Now, it has been discovered that a new general class of compounds in combination with polymerization catalysts are capable of improving reactor operability. Thus, it is possible to have a polymerization process capable of operating continuously with enhanced reactor operability and at the same time produce new and improved polymers. Now it is also possible to have a continuously operating polymerization process with more stable catalyst productivities, reduced fouling/sheeting tendencies and increased duration of operation.

#### **SUMMARY OF THE INVENTION**

**[0012]** This invention provides a method of making a new and improved catalyst composition and for its use in a polymerizing process. The method comprises the step of combining, contacting, blending and/or mixing a catalyst system, preferably a supported catalyst system, with a gelling agent. In one embodiment the catalyst system comprises a conventional-type transition metal catalyst compound. In the most preferred embodiment the catalyst system comprises a bulky ligand metallocene catalyst compound. The combination of the catalyst system and the gelling agent is useful in any olefin polymerization process. The preferred polymerization processes are a gas phase or a slurry phase process, most preferably a gas phase process.

**[0013]** In another embodiment, the invention provides for a method of making a catalyst composition useful for the polymerization of olefin(s), the method including combining, contacting, blending and/or mixing a polymerization catalyst with at least one gelling agent.

**[0014]** In one preferred embodiment, the invention is directed to a catalyst composition comprising a catalyst compound, preferably a conventional-type transition metal catalyst compound, more preferably a bulky ligand metallocene catalyst compound, an activator and/or cocatalyst, a carrier, and a gelling agent.

**[0015]** In yet another embodiment, the invention relates to a process for polymerizing olefin(s) in the presence of a catalyst composition comprising a

polymerization catalyst and a gelling agent, preferably the polymerization catalyst comprises a carrier, more preferably the polymerization catalyst comprises one or more of a combination of a conventional-type catalyst compound and/or a bulky ligand metallocene catalyst compound.

- 5   **[0016]**        In still another embodiment, the invention provides for a process for polymerizing olefin(s) in the presence of a polymerization catalyst having been combined, contacted, blended, or mixed with at least one gelling agent.

#### **DETAILED DESCRIPTION OF THE INVENTION**

- 10   **[0017]**        The invention is directed to a method for making a catalyst composition and to the catalyst composition itself. The invention also relates to a polymerization process having improved operability and product capabilities using the catalyst composition. It has been surprisingly discovered that using a gelling agent in combination with a catalyst system results in a substantially improved polymerization process.

15   **[0018]**        The general class of compounds that are useful in the present invention are gelling agents, which are compounds that are capable of forming thermally - reversible viscoelastic liquid-like or solid-like materials (organogels) in organic liquids (for example, in n-hexane). That is, compounds useful in the invention characteristically form organogels. Specifically, organogels are formed by warming gelling agents in an organic liquid until they dissolve and wherein after dissolution, the solution containing the gelling agent is allowed to stand or cooled until gelation occurs wherein the agent becomes a colloidal aggregate that immobilizes the liquid to a variant degree.

#### **CATALYST COMPONENTS AND CATALYST SYSTEMS**

- 25   **[0019]**        All polymerization catalysts including conventional-type transition metal catalysts are suitable for use in the polymerizing process of the invention. But processes that use bulky ligand and/or bridged bulky ligand metallocene catalysts are particularly preferred. The following is a non-limiting description of the various polymerization catalysts useful in the invention.

##### **Conventional Transition Metal Catalysts**

- 35   **[0020]**        Conventional transition metal catalysts are those traditional Ziegler-Natta catalysts and Phillips-type chromium catalyst well known in the art. Examples of conventional transition metal catalysts are discussed in U.S. Patent Nos. 4,115,639; 4,077,904; 4,482,687; 4,564,605; 4,721,763; 4,879,359; and 4,960,741, all of which are herein fully incorporated by reference. The conventional transition metal catalyst

compounds that may be used in the present invention include transition metal compounds from Groups III to VIII, preferably IVB to VIB of the Periodic Table of Elements.

**[0021]** These conventional transition metal catalysts may be represented by the formula:  $MR_x$ , where M is a metal from Groups IIIB to VIII, preferably Group IVB, more preferably titanium; R is a halogen or a hydrocarbyloxy group; and x is the valence of the metal M. Non-limiting examples of R include alkoxy, phenoxy, bromide, chloride and fluoride. Non-limiting examples of conventional transition metal catalysts where M is titanium include  $TiCl_4$ ,  $TiBr_4$ ,  $Ti(OC_2H_5)_3Cl$ ,  $Ti(OC_2H_5)Cl_3$ ,  $Ti(OC_4H_9)_3Cl$ ,  $Ti(OC_3H_7)_2Cl_2$ ,  $Ti(OC_2H_5)_2Br_2$ ,  $TiCl_3 \cdot 1/3AlCl_3$  and  $Ti(OC_{12}H_{25})Cl_3$ .

**[0022]** Conventional-type transition metal catalyst compounds based on magnesium/titanium electron-donor complexes that are useful in the invention are described in, for example, U.S. Patent Nos. 4,302,565 and 4,302,566, which are herein fully incorporate by reference. The  $MgTiCl_6$  (ethyl acetate)<sub>4</sub> derivative is particularly preferred. British Patent Application 2,105,355, herein incorporated by reference, describes various conventional-type vanadium catalyst compound.

**[0023]** Conventional chromium catalyst compounds, often referred to as Phillips-type catalysts, suitable for use in the present invention include  $CrO_3$ , chromocene, silyl chromate, chromyl chloride ( $CrO_2Cl_2$ ), chromium-2-ethyl-hexanoate, chromium acetylacetonate ( $Cr(AcAc)_3$ ), and the like. Non-limiting examples are disclosed in U.S. Patent Nos. 2,285,721, 3,242,099 and 3,231,550, which are herein fully incorporated by reference.

**[0024]** Still other conventional transition metal catalyst compounds and catalyst systems suitable for use in the present invention are disclosed in U.S. Patent Nos. 4,124,532, 4,302,565, 4,302,566 and 5,763,723 and published EP-A2 0 416 815 A2 and EP-A1 0 420 436, which are all herein incorporated by reference.

**[0025]** Other catalysts may include cationic catalysts such as  $AlCl_3$ , and other cobalt and iron catalysts well known in the art.

**[0026]** Typically, these conventional transition metal catalyst compounds excluding some conventional chromium catalyst compounds are activated with one or more of the conventional cocatalysts described below.

### **Conventional Cocatalysts**

**[0027]** Conventional cocatalyst compounds for the above conventional transition metal catalyst compounds may be represented by the formula  $M^3M^4_vX^2_cR^3_{b-c}$ , wherein  $M^3$  is a metal from Group IA, IIA, IIB and IIIA of the Periodic Table of Elements;  $M^4$  is a metal of Group IA of the Periodic Table of Elements; v is a number from 0 to 1; each  $X^2$  is any halogen; c is a number from 0 to 3; each  $R^3$  is a monovalent hydrocarbon

radical or hydrogen; b is a number from 1 to 4; and wherein b minus c is at least 1. Other conventional-type organometallic cocatalyst compounds for the above conventional-type transition metal catalysts have the formula  $M^3R^3_k$ , where  $M^3$  is a Group IA, IIA, IIB or IIIA metal, such as lithium, sodium, beryllium, barium, boron, aluminum, zinc, cadmium, and gallium; k equals 1, 2 or 3 depending upon the valency of  $M^3$  which valency in turn normally depends upon the particular Group to which  $M^3$  belongs; and each  $R^3$  may be any monovalent hydrocarbon radical.

**[0028]** Non-limiting examples of conventional-type organometallic cocatalyst compounds of Group IA, IIA, IIB and IIIA useful with the conventional-type catalyst compounds described above include methyllithium, butyllithium, dihexylmercury, butylmagnesium, diethylcadmium, benzylpotassium, diethylzinc, tri-n-butylaluminum, diisobutyl ethylboron, diethylcadmium, di-n-butylzinc and tri-n-amyloboron, and, in particular, the aluminum alkyls, such as tri-hexyl-aluminum, triethylaluminum, trimethylaluminum, and tri-isobutylaluminum. Other conventional-type cocatalyst compounds include mono-organohalides and hydrides of Group IIA metals, and mono- or di-organohalides and hydrides of Group IIIA metals. Non-limiting examples of such conventional-type cocatalyst compounds include di-isobutylaluminum bromide, isobutylboron dichloride, methyl magnesium chloride, ethylberyllium chloride, ethylcalcium bromide, di-isobutylaluminum hydride, methylcadmium hydride, diethylboron hydride, hexylberyllium hydride, dipropylboron hydride, octylmagnesium hydride, butylzinc hydride, dichloroboron hydride, di-bromo-aluminum hydride and bromocadmium hydride. Conventional-type organometallic cocatalyst compounds are known to those in the art and a more complete discussion of these compounds may be found in U.S. Patent Nos. 3,221,002 and 5,093,415, which are herein fully incorporated by reference.

**[0029]** For purposes of this patent specification and appended claims, conventional transition metal catalyst compounds exclude those bulky ligand metallocene catalyst compounds discussed below.

### **Bulky Ligand Metallocene Catalyst Compounds**

**[0030]** Generally, bulky ligand metallocene catalyst compounds include half and full sandwich compounds having one or more bulky ligands bonded to at least one metal atom. Typical bulky ligand metallocene compounds are generally described as containing one or more bulky ligand(s) and one or more leaving group(s) bonded to at least one metal atom. In one preferred embodiment, at least one bulky ligand is  $\eta$ -bonded to the metal atom, most preferably  $\eta^5$ -bonded to the metal atom.



**[0031]** The bulky ligands are generally represented by one or more open, acyclic, or fused ring(s) or ring system(s) or a combination thereof. These bulky ligands, preferably the ring(s) or ring system(s) are typically composed of atoms selected from Groups 13 to 16 atoms of the Periodic Table of Elements, preferably the atoms are selected from the group consisting of carbon, nitrogen, oxygen, silicon, sulfur, phosphorous, germanium, boron and aluminum or a combination thereof. Most preferably the ring(s) or ring system(s) are composed of carbon atoms such as but not limited to those cyclopentadienyl ligands or cyclopentadienyl-type ligand structures or other similar functioning ligand structure such as a pentadiene, a cyclooctatetraendiyl or an imide ligand. The metal atom is preferably selected from Groups 3 through 15 and the lanthanide or actinide series of the Periodic Table of Elements. Preferably the metal is a transition metal from Groups 4 through 12, more preferably Groups 4, 5 and 6, and most preferably the transition metal is from Group 4.

**[0032]** In one embodiment, the bulky ligand metallocene catalyst compounds of the invention are represented by the formula:



where M is a metal atom from the Periodic Table of the Elements and may be a Group 3 to 12 metal or from the lanthanide or actinide series of the Periodic Table of Elements, preferably M is a Group 4, 5 or 6 transition metal, more preferably M is a Group 4 transition metal, even more preferably M is zirconium, hafnium or titanium. The bulky ligands,  $L^A$  and  $L^B$ , are open, acyclic or fused ring(s) or ring system(s) and are any ancillary ligand system, including unsubstituted or substituted, cyclopentadienyl ligands or cyclopentadienyl-type ligands, heteroatom substituted and/or heteroatom containing cyclopentadienyl-type ligands. Non-limiting examples of bulky ligands include cyclopentadienyl ligands, cyclopentaphenanthrene ligands, indenyl ligands, benzindenyl ligands, fluorenyl ligands, octahydrofluorenyl ligands, cyclooctatetraendiyl ligands, cyclopentacyclododecene ligands, azenyl ligands, azulene ligands, pentalene ligands, phosphoyl ligands, phosphinimine (WO 99/40125), pyrrolyl ligands, pyrolyl ligands, carbazoyl ligands, borabenzene ligands and the like, including hydrogenated versions thereof, for example tetrahydroindenyl ligands. In one embodiment,  $L^A$  and  $L^B$  may be any other ligand structure capable of  $\eta$ -bonding to M, preferably  $\eta^3$ -bonding to M and most preferably  $\eta^5$ -bonding. In yet another embodiment, the atomic molecular weight (MW) of  $L^A$  or  $L^B$  exceeds 60 a.m.u., preferably greater than 65 a.m.u. In another embodiment,  $L^A$  and  $L^B$  may comprise one or more heteroatoms, for example, nitrogen, silicon, boron, germanium, sulfur and phosphorous, in combination with carbon atoms to form an open, acyclic, or preferably a fused, ring or ring system, for example, a heterocyclopentadienyl ancillary ligand. Other  $L^A$  and  $L^B$  bulky ligands include but are not

limited to bulky amides, phosphides, alkoxides, aryloxides, imides, carbolides, borollides, porphyrins, phthalocyanines, corrins and other polyazomacrocycles. Independently, each  $L^A$  and  $L^B$  may be the same or different type of bulky ligand that is bonded to M. In one embodiment of formula (I) only one of either  $L^A$  or  $L^B$  is present.

5 **[0033]** Independently, each  $L^A$  and  $L^B$  may be unsubstituted or substituted with a combination of substituent groups R. Non-limiting examples of substituent groups R include one or more from the group selected from hydrogen, or linear, branched alkyl radicals, or alkenyl radicals, alkynyl radicals, cycloalkyl radicals or aryl radicals, acyl radicals, aroyl radicals, alkoxy radicals, aryloxy radicals, alkylthio radicals, dialkylamino radicals, alkoxy carbonyl radicals, aryloxy carbonyl radicals, carbomoyl radicals, alkyl- or dialkyl- carbamoyl radicals, acyloxy radicals, acylamino radicals, aroylamino radicals, straight, branched or cyclic, alkylene radicals, or combination thereof. In a preferred embodiment, substituent groups R have up to 50 non-hydrogen atoms, preferably from 1 to 30 carbon, that can also be substituted with halogens or heteroatoms or the like. Non-  
15 limiting examples of alkyl substituents R include methyl, ethyl, propyl, butyl, pentyl, hexyl, cyclopentyl, cyclohexyl, benzyl or phenyl groups and the like, including all their isomers, for example tertiary butyl, isopropyl, and the like. Other hydrocarbyl radicals include fluoromethyl, fluoroethyl, difluoroethyl, iodopropyl, bromohexyl, chlorobenzyl and hydrocarbyl substituted organometalloid radicals including trimethylsilyl, trimethylgermyl, methyldiethylsilyl and the like; and halocarbyl-substituted organometalloid radicals including tris(trifluoromethyl)-silyl, methyl-  
20 bis(difluoromethyl)silyl, bromomethyldimethylgermyl and the like; and disubstituted boron radicals including dimethylboron for example; and disubstituted pnictogen radicals including dimethylamine, dimethylphosphine, diphenylamine, methylphenylphosphine, chalcogen radicals including methoxy, ethoxy, propoxy, phenoxy, methylsulfide and ethylsulfide. Non-hydrogen substituents R include the atoms carbon, silicon, boron, aluminum, nitrogen, phosphorous, oxygen, tin, sulfur, germanium and the like, including olefins such as but not limited to olefinically unsaturated substituents including vinyl-terminated ligands, for example but-3-enyl, prop-2-enyl, hex-5-enyl and the like. Also,  
25 at least two R groups, preferably two adjacent R groups, are joined to form a ring structure having from 3 to 30 atoms selected from carbon, nitrogen, oxygen, phosphorous, silicon, germanium, aluminum, boron or a combination thereof. Also, a substituent group R group such as 1-butanyl may form a carbon sigma bond to the metal M.

35 **[0034]** Other ligands may be bonded to the metal M, such as at least one leaving group Q. For the purposes of this patent specification and appended claims the term "leaving group" is any ligand that can be abstracted from a bulky ligand metallocene

catalyst compound to form a bulky ligand metallocene catalyst cation capable of polymerizing one or more olefin(s). In one embodiment, Q is a monoanionic labile ligand having a sigma-bond to M. Depending on the oxidation state of the metal, the value for n is 0, 1 or 2 such that formula (I) above represents a neutral bulky ligand metallocene catalyst compound.

**[0035]** Non-limiting examples of Q ligands include weak bases such as amines, phosphines, ethers, carboxylates, dienes, hydrocarbyl radicals having from 1 to 20 carbon atoms, hydrides or halogens and the like or a combination thereof. In another embodiment, two or more Q's form a part of a fused ring or ring system. Other examples of Q ligands include those substituents for R as described above and including cyclobutyl, cyclohexyl, heptyl, tolyl, trifluoromethyl, tetramethylene, pentamethylene, methyldiene, methoxy, ethoxy, propoxy, phenoxy, bis(N-methylanilide), dimethylamide, dimethylphosphide radicals and the like.

**[0036]** In one embodiment, the bulky ligand metallocene catalyst compounds of the invention include those of formula (I) where  $L^A$  and  $L^B$  are bridged to each other by at least one bridging group, A, such that the formula is represented by



**[0037]** These bridged compounds represented by formula (II) are known as bridged, bulky ligand metallocene catalyst compounds.  $L^A$ ,  $L^B$ , M, Q and n are as defined above. Non-limiting examples of bridging group A include bridging groups containing at least one Group 13 to 16 atom, often referred to as a divalent moiety such as but not limited to at least one of a carbon, oxygen, nitrogen, silicon, aluminum, boron, germanium and tin atom or a combination thereof. Preferably bridging group A contains a carbon, silicon or germanium atom, most preferably A contains at least one silicon atom or at least one carbon atom. The bridging group A may also contain substituent groups R as defined above including halogens and iron. Non-limiting examples of bridging group A may be represented by  $R'_2C$ ,  $R'_2Si$ ,  $R'_2Si R'_2Si$ ,  $R'_2Ge$ ,  $R'_2P$ , where  $R'$  is independently, a radical group which is hydride, hydrocarbyl, substituted hydrocarbyl, halocarbyl, substituted halocarbyl, hydrocarbyl-substituted organometalloid, halocarbyl-substituted organometalloid, disubstituted boron, disubstituted pnictogen, substituted chalcogen, or halogen or two or more  $R'$  may be joined to form a ring or ring system. In one embodiment, the bridged, bulky ligand metallocene catalyst compounds of formula (II) have two or more bridging groups A (EP 664 301 B1).


**[0038]** In one embodiment, the bulky ligand metallocene catalyst compounds are those where the R substituents on the bulky ligands  $L^A$  and  $L^B$  of formulas (I) and (II) are substituted with the same or different number of substituents on each of the bulky

ligands. In another embodiment, the bulky ligands  $L^A$  and  $L^B$  of formulas (I) and (II) are different from each other.

**[0039]** Other bulky ligand metallocene catalyst compounds and catalyst systems useful in the invention may include those described in U.S. Patent Nos. 5,064,802, 5,145,819, 5,149,819, 5,243,001, 5,239,022, 5,276,208, 5,296,434, 5,321,106, 5,329,031, 5,304,614, 5,677,401, 5,723,398, 5,753,578, 5,854,363, 5,856,547, 5,858,903, 5,859,158, 5,900,517, 5,939,503 and 5,962,718 and PCT publications WO 93/08221, WO 93/08199, WO 95/07140, WO 98/11144, WO 98/41530, WO 98/41529, WO 98/46650, WO 99/02540 and WO 99/14221 and European publications EP-A-0 578 838, EP-A-0 638 595, EP-B-0 513 380, EP-A1-0 816 372, EP-A2-0 839 834, EP-B1-0 632 819, EP-B1-0 739 361, EP-B1-0 748 821 and EP-B1-0 757 996, all of which are herein fully incorporated by reference.

**[0040]** In one embodiment, bulky ligand metallocene catalysts compounds useful in the invention include bridged heteroatom, mono-bulky ligand metallocene compounds. These types of catalysts and catalyst systems are described in, for example, PCT publication WO 92/00333, WO 94/07928, WO 91/04257, WO 94/03506, WO96/00244, WO 97/15602 and WO 99/20637 and U.S. Patent Nos. 5,057,475, 5,096,867, 5,055,438, 5,198,401, 5,227,440 and 5,264,405 and European publication EP-A-0 420 436, all of which are herein fully incorporated by reference.

**[0041]** In this embodiment, the bulky ligand metallocene catalyst compound is represented by the formula:



where M is a Group 3 to 16 metal atom or a metal selected from the Group of actinides and lanthanides of the Periodic Table of Elements, preferably M is a Group 4 to 12 transition metal, and more preferably M is a Group 4, 5 or 6 transition metal, and most preferably M is a Group 4 transition metal in any oxidation state, especially titanium;  $L^C$  is a substituted or unsubstituted bulky ligand bonded to M; J is bonded to M; A is bonded to  $L^C$  and J; J is a heteroatom ancillary ligand; and A is a bridging group; Q is a univalent anionic ligand; and n is the integer 0, 1 or 2. In formula (III) above,  $L^C$ , A and J form a fused ring system. In an embodiment,  $L^C$  of formula (III) is as defined above for  $L^A$ , A, M and Q of formula (III) are as defined above in formula (I).

In formula (III) J is a heteroatom containing ligand in which J is an element with a coordination number of three from Group 15 or an element with a coordination number of two from Group 16 of the Periodic Table of Elements. Preferably J contains a nitrogen, phosphorus, oxygen or sulfur atom with nitrogen being most preferred.

**[0042]** In another embodiment, the bulky ligand type metallocene catalyst compound is a complex of a metal, preferably a transition metal, a bulky ligand,

preferably a substituted or unsubstituted pi-bonded ligand, and one or more heteroallyl moieties, such as those described in U.S. Patent Nos. 5,527,752 and 5,747,406 and EP-B1-0 735 057, all of which are herein fully incorporated by reference.

- 5 **[0043]** In an embodiment, the bulky ligand metallocene catalyst compound is represented by the formula:



- where M is a Group 3 to 16 metal, preferably a Group 4 to 12 transition metal, and most preferably a Group 4, 5 or 6 transition metal;  $L^D$  is a bulky ligand that is  
10 bonded to M; each Q is independently bonded to M and  $Q_2(YZ)$  forms a uncharged polydentate ligand; A or Q is a univalent anionic ligand also bonded to M; X is a univalent anionic group when n is 2 or X is a divalent anionic group when n is 1; n is 1 or 2.

- [0044]** In formula (IV), L and M are as defined above for formula (I). Q is  
15 as defined above for formula (I), preferably Q is selected from the group consisting of -O-, -NR-, -CR<sub>2</sub>- and -S-; Y is either C or S; Z is selected from the group consisting of -OR-, -NR<sub>2</sub>-, -CR<sub>3</sub>-, -SR-, -SiR<sub>3</sub>-, -PR<sub>2</sub>-, -H, and substituted or unsubstituted aryl groups, with the proviso that when Q is -NR- then Z is selected from one of the group consisting of -OR-, -NR<sub>2</sub>-, -SR-, -SiR<sub>3</sub>-, -PR<sub>2</sub>- and -H; R is  
20 selected from a group containing carbon, silicon, nitrogen, oxygen, and/or phosphorus, preferably where R is a hydrocarbon group containing from 1 to 20 carbon atoms, most preferably an alkyl, cycloalkyl, or an aryl group; n is an integer from 1 to 4, preferably 1 or 2; X is a univalent anionic group when n is 2 or X is a divalent anionic group when n is 1; preferably X is a carbamate, carboxylate, or  
25 other heteroallyl moiety described by the Q, Y and Z combination.

- [0045]** In another embodiment of the invention, the bulky ligand metallocene-type catalyst compounds are heterocyclic ligand complexes where the bulky ligands, the ring(s) or ring system(s), include one or more heteroatoms or a combination thereof. Non-limiting examples of heteroatoms include a Group 13 to  
30 16 element, preferably nitrogen, boron, sulfur, oxygen, aluminum, silicon, phosphorous and tin. Examples of these bulky ligand metallocene catalyst compounds are described in WO 96/33202, WO 96/34021, WO 97/17379, WO 98/22486 and WO 99/40095 (dicarbamoyl metal complexes) and EP-A1-0 874 005 and U.S. Patent No. 5,637,660, 5,539,124, 5,554,775, 5,756,611, 5,233,049,  
35 5,744,417, and 5,856,258 all of which are herein incorporated by reference.

**[0046]** In another embodiment, the bulky ligand metallocene catalyst compounds are those complexes known as transition metal catalysts based on

bidentate ligands containing pyridine or quinoline moieties, such as those described in U.S. Application Serial No. 09/103,620 filed June 23, 1998, which is herein incorporated by reference. In another embodiment, the bulky ligand metallocene catalyst compounds are those described in PCT publications WO 99/01481 and WO 98/42664, which are fully incorporated herein by reference.

**[0047]** In one embodiment, the bulky ligand metallocene catalyst compound is represented by the formula:



where M is a metal selected from Group 3 to 13 or lanthanide and actinide series of the Periodic Table of Elements; Q is bonded to M and each Q is a monovalent, bivalent, or trivalent anion; X and Y are bonded to M; one or more of X and Y are heteroatoms, preferably both X and Y are heteroatoms; Y is contained in a heterocyclic ring J, where J comprises from 2 to 50 non-hydrogen atoms, preferably 2 to 30 carbon atoms; Z is bonded to X, where Z comprises 1 to 50 non-hydrogen atoms, preferably 1 to 50 carbon atoms, preferably Z is a cyclic group containing 3 to 50 atoms, preferably 3 to 30 carbon atoms; t is 0 or 1; when t is 1, A is a bridging group joined to at least one of X, Y or J, preferably X and J; q is 1 or 2; n is an integer from 1 to 4 depending on the oxidation state of M. In one embodiment, where X is oxygen or sulfur, then Z is optional. In another embodiment, where X is nitrogen or phosphorous then Z is present. In an embodiment, Z is preferably an aryl group, more preferably a substituted aryl group.

#### **Other Bulky Ligand Metallocene Catalyst Compounds**

**[0048]** It is within the scope of this invention, in one embodiment, that the bulky ligand metallocene catalyst compounds include complexes of  $Ni^{2+}$  and  $Pd^{2+}$  described in the articles Johnson, et al., "New Pd(II)- and Ni(II)- Based Catalysts for Polymerization of Ethylene and  $\alpha$ -Olefins", *J. Am. Chem. Soc.* 1995, 117, 6414-6415 and Johnson, et al., "Copolymerization of Ethylene and Propylene with Functionalized Vinyl Monomers by Palladium(II) Catalysts", *J. Am. Chem. Soc.*, 1996, 118, 267-268, and WO 96/23010 published August 1, 1996, WO 99/02472, U.S. Patent Nos. 5,852,145, 5,866,663 and 5,880,241, which are all herein fully incorporated by reference. These complexes can be either dialkyl ether adducts, or alkylated reaction products of the described dihalide complexes that can be activated to a cationic state by the activators of this invention described below.

**[0049]** Also included as bulky ligand metallocene catalyst are those diimine based ligands of Group 8 to 10 metal compounds disclosed in PCT publications WO

96/23010 and WO 97/48735 and Gibson, et. al., Chem. Comm., pp. 849-850 (1998), all of which are herein incorporated by reference.

**[0050]** Other bulky ligand metallocene catalysts are those Group 5 and 6 metal imido complexes described in EP-A2-0 816 384 and U.S. Patent No.

5 5,851,945, which is incorporated herein by reference. In addition, bulky ligand metallocene catalysts include bridged bis(arylamido) Group 4 compounds described by D.H. McConville, et al., in *Organometallics* 1195, 14, 5478-5480, which is herein incorporated by reference. In addition, bridged bis(amido) catalyst compounds are described in WO 96/27439, which is herein incorporated by reference. Other bulky  
10 ligand metallocene catalysts are described as bis(hydroxy aromatic nitrogen ligands) in U.S. Patent No. 5,852,146, which is incorporated herein by reference. Other metallocene catalysts containing one or more Group 15 atoms include those described in WO 98/46651, which is herein incorporated herein by reference. Still another metallocene bulky ligand metallocene catalysts include those multinuclear  
15 bulky ligand metallocene catalysts as described in WO 99/20665, which is incorporated herein by reference.

**[0051]** It is also contemplated that in one embodiment, the bulky ligand metallocene catalysts of the invention described above include their structural or optical or enantiomeric isomers (meso and racemic isomers, for example see U.S.  
20 Patent No. 5,852,143, incorporated herein by reference) and mixtures thereof.

#### **Activator and Activation Methods for the Bulky Ligand Metallocene Catalyst Compounds**

**[0052]** The above described bulky ligand metallocene catalyst compounds are  
25 typically activated in various ways to yield catalyst compounds having a vacant coordination site that will coordinate, insert, and polymerize olefin(s).

**[0053]** For the purposes of this patent specification and appended claims, the term "activator" is defined to be any compound or component or method which can activate any of the bulky ligand metallocene catalyst compounds or other catalyst  
30 compounds of the invention as described above. Non-limiting activators, for example may include a Lewis acid or a non-coordinating ionic activator or ionizing activator or any other compound including Lewis bases, aluminum alkyls, conventional-type cocatalysts and combinations thereof that can convert a neutral bulky ligand metallocene catalyst compound to a catalytically active bulky ligand metallocene cation. It is within  
35 the scope of this invention to use alumoxane or modified alumoxane as an activator, and/or to also use ionizing activators, neutral or ionic, such as tri (n-butyl) ammonium tetrakis (pentafluorophenyl) boron, a trisperfluorophenyl boron metalloid precursor or a

trisperfluoronaphtyl boron metalloid precursor, polyhalogenated heteroborane anions (WO 98/43983) or combination thereof, that would ionize the neutral bulky ligand metallocene catalyst compound.

**[0054]** In one embodiment, an activation method using ionizing ionic compounds not containing an active proton but capable of producing both a bulky ligand metallocene catalyst cation and a non-coordinating anion are also contemplated, and are described in EP-A- 0 426 637, EP-A- 0 573 403 and U.S. Patent No. 5,387,568, which are all herein incorporated by reference.

**[0055]** There are a variety of methods for preparing alumoxane and modified alumoxanes, non-limiting examples of which are described in U.S. Patent No. 4,665,208, 4,952,540, 5,091,352, 5,206,199, 5,204,419, 4,874,734, 4,924,018, 4,908,463, 4,968,827, 5,308,815, 5,329,032, 5,248,801, 5,235,081, 5,157,137, 5,103,031, 5,391,793, 5,391,529, 5,693,838, 5,731,253, 5,731,451, 5,744,656, 5,847,177, 5,854,166, 5,856,256 and 5,939,346 and European publications EP-A-0 561 476, EP-B1-0 279 586, EP-A-0 594-218 and EP-B1-0 586 665, and PCT publication WO 94/10180, all of which are herein fully incorporated by reference.

**[0056]** Organoaluminum compounds useful as activators include trimethylaluminum, triethylaluminum, triisobutylaluminum, tri-n-hexylaluminum, tri-n-octylaluminum and the like.

**[0057]** Ionizing compounds may contain an active proton, or some other cation associated with but not coordinated to or only loosely coordinated to the remaining ion of the ionizing compound. Such compounds and the like are described in European publications EP-A-0 570 982, EP-A-0 520 732, EP-A-0 495 375, EP-B1-0 500 944, EP-A-0 277 003 and EP-A-0 277 004, and U.S. Patent Nos. 5,153,157, 5,198,401, 5,066,741, 5,206,197, 5,241,025, 5,384,299 and 5,502,124 and U.S. Patent Application Serial No. 08/285,380, filed August 3, 1994, all of which are herein fully incorporated by reference.

**[0058]** Other activators include those described in PCT publication WO 98/07515 such as tris (2, 2', 2''- nonafluorobiphenyl) fluoroaluminate, which publication is fully incorporated herein by reference. Combinations of activators are also contemplated by the invention, for example, alumoxanes and ionizing activators in combinations, see for example, EP-B1 0 573 120, PCT publications WO 94/07928 and WO 95/14044 and U.S. Patent Nos. 5,153,157 and 5,453,410 all of which are herein fully incorporated by reference. WO 98/09996 incorporated herein by reference describes activating bulky ligand metallocene catalyst compounds with perchlorates, periodates and iodates including their hydrates. WO 98/30602 and WO 98/30603 incorporated by reference describe the use of lithium (2,2'-bisphenyl-ditrimethylsilicate)•4THF as an



activator for a bulky ligand metallocene catalyst compound. WO 99/18135 incorporated herein by reference describes the use of organo-boron-aluminum activators. EP-B1-0 781 299 describes using a silylium salt in combination with a non-coordinating compatible anion. Also, methods of activation such as using radiation (see EP-B1-0 615 981 herein incorporated by reference), electro-chemical oxidation, and the like are also contemplated as activating methods for the purposes of rendering the neutral bulky ligand metallocene catalyst compound or precursor to a bulky ligand metallocene cation capable of polymerizing olefins. Other activators or methods for activating a bulky ligand metallocene catalyst compound are described in for example, U.S. Patent Nos. 5,849,852, 5,859,653 and 5,869,723 and WO 98/32775, WO 99/42467 (dioctadecylmethylammonium-bis(tris(pentafluorophenyl)borane)benzimidazolidine), which are herein incorporated by reference.

**[0059]** It is also within the scope of this invention that one or more of the above described bulky ligand metallocene catalyst compounds or conventional catalyst compounds can be combined with one or more activators or activation methods described above.

**[0060]** It is further contemplated by the invention that other catalysts can be combined with the bulky ligand metallocene catalyst compounds of the invention. For example, see U.S. Patent Nos. 4,937,299, 4,935,474, 5,281,679, 5,359,015, 5,470,811, and 5,719,241 all of which are herein fully incorporated herein reference. It is also contemplated that any one of the bulky ligand metallocene catalyst compounds of the invention have at least one fluoride or fluorine containing leaving group as described in U.S. Application Serial No. 09/191,916 filed November 13, 1998.

**[0061]** In another embodiment of the invention one or more bulky ligand metallocene catalyst compounds or catalyst systems may be used in combination with one or more conventional-type catalyst compounds or catalyst systems. Non-limiting examples of mixed catalysts and catalyst systems are described in U.S. Patent Nos. 4,159,965, 4,325,837, 4,701,432, 5,124,418, 5,077,255, 5,183,867, 5,391,660, 5,395,810, 5,691,264, 5,723,399 and 5,767,031 and PCT Publication WO 96/23010 published August 1, 1996, all of which are herein fully incorporated by reference.

#### **Method for Supporting**

**[0062]** The above described bulky ligand metallocene catalyst compounds and catalyst systems and conventional-type transition metal catalyst compounds and catalyst systems may be combined with one or more support materials or carriers using one of the support methods well known in the art or as described below. In the preferred

embodiment, the method of the invention uses a polymerization catalyst in a supported form. For example, in a most preferred embodiment, a bulky ligand metallocene catalyst compound or catalyst system is in a supported form, for example deposited on, contacted with, or incorporated within, adsorbed or absorbed in a support or carrier.

5 **[0063]** The terms "support" or "carrier" are used interchangeably and are any porous or non-porous support material, preferably a porous support material, for example, talc, inorganic oxides and inorganic chlorides. Other carriers include resinous support materials such as polystyrene, a functionalized or crosslinked organic supports, such as polystyrene divinyl benzene polyolefins or polymeric compounds, or any other  
10 organic or inorganic support material and the like, or mixtures thereof.

**[0064]** The preferred carriers are inorganic oxides that include those Group 2, 3, 4, 5, 13 or 14 metal oxides. The preferred supports includes silica, alumina, silica-alumina, magnesium chloride, and mixtures thereof. Other useful supports include magnesia, titania, zirconia, montmorillonite and the like. Also, combinations of these  
15 support materials may be used, for example, silica-chromium and silica-titania.

**[0065]** It is preferred that the carrier, most preferably an inorganic oxide, has a surface area in the range of from about 10 to about 700 m<sup>2</sup>/g, pore volume in the range of from about 0.1 to about 4.0 cc/g and average particle size in the range of from about 10 to about 500 µm. More preferably, the surface area of the carrier is in the range of from about 50 to about 500 m<sup>2</sup>/g, pore volume of from about 0.5 to about 3.5 cc/g and average  
20 particle size of from about 20 to about 200 µm. Most preferably the surface area of the carrier is in the range of from about 100 to about 400 m<sup>2</sup>/g, pore volume from about 0.8 to about 3.0 cc/g and average particle size is from about 20 to about 100 µm. The average pore size of a carrier of the invention is typically in the range of from about 10 Å to 1000Å, preferably 50 Å to about 500Å, and most preferably 75 Å to about 350Å.  
25

**[0066]** Examples of supporting the bulky ligand metallocene catalyst systems of the invention are described in U.S. Patent Nos. 4,701,432, 4,808,561, 4,912,075, 4,925,821, 4,937,217, 5,008,228, 5,238,892, 5,240,894, 5,332,706, 5,346,925, 5,422,325, 5,466,649, 5,466,766, 5,468,702, 5,529,965, 5,554,704, 5,629,253, 5,639,835, 5,625,015,  
30 5,643,847, 5,665,665, 5,698,487, 5,714,424, 5,723,400, 5,723,402, 5,731,261, 5,759,940, 5,767,032 and 5,770,664 and U.S. Application Serial Nos. 271,598 filed July 7, 1994 and 788,736 filed January 23, 1997 and PCT publications WO 95/32995, WO 95/14044, WO 96/06187 and WO 97/02297 all of which are herein fully incorporated by reference.

**[0067]** Examples of supporting the conventional-type catalyst systems of the  
35 invention are described in U.S. Patent No. 4,894,424, 4,376,062, 4,395,359, 4,379,759, 4,405,495 4,540758 and 5,096,869, all of which are herein incorporated by reference.

**[0068]** It is contemplated that the bulky ligand metallocene catalyst compounds of the invention may be deposited on the same or separate supports together with an activator, or the activator may be used in an unsupported form, or may be deposited on a support different from the supported bulky ligand metallocene catalyst compounds of the invention, or any combination thereof.

**[0069]** There are various other methods in the art for supporting a polymerization catalyst compound or catalyst system of the invention. For example, the bulky ligand metallocene catalyst compound of the invention may contain a polymer bound ligand as described in U.S. Patent Nos. 5,473,202 and 5,770,755, which is herein fully incorporated by reference; the bulky ligand metallocene catalyst system of the invention may be spray dried as described in U.S. Patent No. 5,648,310, which is herein fully incorporated by reference; the support used with the bulky ligand metallocene catalyst system of the invention is functionalized as described in European publication EP-A-0 802 203, which is herein fully incorporated by reference; or at least one substituent or leaving group is selected as described in U.S. Patent No. 5,688,880, which is herein fully incorporated by reference.

**[0070]** In a preferred embodiment, the invention provides for a supported bulky ligand metallocene catalyst system that includes a surface modifier that is used in the preparation of the supported catalyst system, as described in PCT publication WO 96/11960 which is herein fully incorporated by reference.

**[0071]** A preferred method for producing the supported bulky ligand metallocene catalyst system of the invention is described below and can be found in U.S. Application Serial Nos. 265,533, filed June 24, 1994 and 265,532, filed June 24, 1994 and PCT publications WO 96/00245 and WO 96/00243 both published January 4, 1996, all of which are herein fully incorporated by reference. In this preferred method, the bulky ligand metallocene catalyst compound is slurried in a liquid to form a metallocene solution and a separate solution is formed containing an activator and a liquid. The liquid may be any compatible solvent or other liquid capable of forming a solution or the like with the bulky ligand metallocene catalyst compounds and/or activator of the invention. In the most preferred embodiment the liquid is a cyclic aliphatic or aromatic hydrocarbon, most preferably toluene. The bulky ligand metallocene catalyst compound and activator solutions are mixed together and added to a porous support or the porous support is added to the solutions such that the total volume of the bulky ligand metallocene catalyst compound solution and the activator solution or the bulky ligand metallocene catalyst compound and activator solution is less than five times the pore volume of the porous support, more preferably less than four times, even more preferably

less than three times; preferred ranges being from 1.1 times to 3.5 times range and most preferably in the 1.2 to 3 times range.

**[0072]** Procedures for measuring the total pore volume of a porous support are well known in the art. Details of one of these procedures is discussed in Volume 1, *Experimental Methods in Catalytic Research* (Academic Press, 1968) (specifically see pages 67-96). This preferred procedure involves the use of a classical BET apparatus for nitrogen absorption. Another method well known in the art is described in Innes, *Total Porosity and Particle Density of Fluid Catalysts By Liquid Titration*, Vol. 28, No. 3, Analytical Chemistry 332-334 (March, 1956).

**[0073]** The mole ratio of the metal of the activator component to the metal of the bulky ligand metallocene catalyst compounds are in the range of between 0.3:1 to 2000:1, preferably 20:1 to 800:1, and most preferably 50:1 to 500:1. Where the activator is an ionizing activator such as those based on the anion tetrakis(pentafluorophenyl)boron, the mole ratio of the metal of the activator component to the metal component of the catalyst is preferably in the range of between 0.3:1 to 3:1.

**[0074]** In one embodiment of the invention, olefin(s), preferably C<sub>2</sub> to C<sub>30</sub> olefin(s) or alpha-olefin(s), preferably ethylene or propylene or combinations thereof are prepolymerized in the presence of the bulky ligand metallocene catalyst system and/or a conventional-type transition metal catalysts of the invention prior to the main polymerization. The prepolymerization can be carried out batchwise or continuously in gas, solution or slurry phase including at elevated pressures. The prepolymerization can take place with any olefin monomer or combination and/or in the presence of any molecular weight controlling agent such as hydrogen. For examples of prepolymerization procedures, see U.S. Patent Nos. 4,748,221, 4,789,359, 4,923,833, 4,921,825, 5,283,278 and 5,705,578 and European publication EP-B-0279 863 and PCT Publication WO 97/44371 all of which are herein fully incorporated by reference. A prepolymerized catalyst system for purposes of this patent specification and appended claim is a supported catalyst system.

### **Gelling Agents**

**[0075]** In the invention, compounds that are useful for combining, contacting and/or mixing with a polymerization catalyst system are generally referred to herein as gelling agents. Gelling agents that are useful in the invention form thermally - reversible viscoelastic liquid-like or solid like materials (organogels) in organic liquids (for example, in n-hexane). Gelling agents form organogels when they are dissolved in an organic liquid and the solution is cooled (or allowed to stand) until gelation occurs

wherein the agent becomes a colloidal aggregate that immobilizes the liquid to a variant degree.

**[0076]** Non-limiting examples of gelling agents or organogelators with such characteristics include: aluminum ortho-phosphates, steroid and anthryl derivatives, amino acid-type gelators, organometallic compounds, quaternary ammonium salts, etc. One preferred gelling agent is tetraoctadecyl ammonium bromide.

**[0077]** Other gelling agents include dihexadecylaluminum ortho phosphate, bicopper tetracarboxylate complex, steroid derivatives such as deoxycholic, cholic, lithocholic acids and their salts, dihydrolanosterol anthryl derivatives, for example 2,3-Bis-n-decyloxyanthracene(DDOA) and related anthraquinone

**[0078]** Cholesteryl 4-(2-anthryloxy) butanoate and cholesteryl anthraquinone-2-carboxylate; organometallic compounds such as copper diketonates and carboxylates; Sorbitol and Polyol derivatives salts as are well known in the art as additives for use with polyolefins.

**[0079]** Other preferred gelling agents include phosphate diester compounds such as, for example,  $(OH)Al(ROPOR')_2$ ;  $(Et)Al(ROPOR')_2$ ;  $(Et)Al(ROPOR)_2$ ; and  $Mg(ROPOR')_2$ , where R is  $C_{12-20}H_{21-37}$  and especially  $C_{18}H_{33}$  and R' is  $CH_3$ .

**[0080]** In one embodiment of the invention, the gelling agent excludes those mono- or di- or tri-carboxylic acid salt with a metal portion from the Periodic Table of Elements.

#### **Method of Preparing the Catalyst Composition**

**[0081]** The method for making the catalyst composition generally involves the combining, contacting, blending, and/or mixing of a catalyst system or polymerization catalyst with a gelling agent.

**[0082]** In one embodiment of the method of the invention, a conventional-type transition metal catalyst and/or a bulky ligand metallocene catalyst is combined, contacted, blended, and/or mixed with at least one gelling agent. In a most preferred embodiment, the conventional-type transition metal catalyst and/or the bulky ligand metallocene catalyst are supported on a carrier.

**[0083]** In another embodiment, the steps of the method of the invention include forming a polymerization catalyst, preferably forming a supported polymerization catalyst, and contacting the polymerization catalyst with at least one gelling agent. In a preferred method, the polymerization catalyst comprises a catalyst compound, an activator or cocatalyst and a carrier, preferably the polymerization catalyst is a supported bulky ligand metallocene catalyst.

**[0084]** In one embodiment of the method of the invention the gelling agent is contacted with the catalyst system, preferably a supported catalyst system, most preferably a supported bulky ligand metallocene catalyst system under ambient temperatures and pressures. Preferably the contact temperature for combining the polymerization catalyst and the gelling agent is in the range of from 0 °C to about 100 °C, more preferably from 15 °C to about 75 °C, most preferably at about ambient temperature and pressure.

**[0085]** In a preferred embodiment, the contacting of the polymerization catalyst and the gelling agent is performed under an inert gaseous atmosphere, such as nitrogen. However, it is contemplated that the combination of the polymerization catalyst and the gelling agent may be performed in the presence of olefin(s), solvents, hydrogen and the like.

**[0086]** In one embodiment, the gelling agent may be added at any stage during the preparation of the polymerization catalyst.

**[0087]** In one embodiment of the method of the invention, the polymerization catalyst and the gelling agent are combined in the presence of a liquid, for example the liquid may be a mineral oil, toluene, hexane, isobutane or a mixture thereof. In a more preferred method the gelling agent is combined with a polymerization catalyst that has been formed in a liquid, preferably in a slurry, or combined with a substantially dry or dried, polymerization catalyst that has been placed in a liquid and reslurried.

**[0088]** In an embodiment, the contact time for the gelling agent and the polymerization catalyst may vary depending on one or more of the conditions, temperature and pressure, the type of mixing apparatus, the quantities of the components to be combined, and even the mechanism for introducing the polymerization catalyst/gelling agent combination into the reactor.

**[0089]** Preferably, the polymerization catalyst, preferably a bulky ligand metallocene catalyst compound and a carrier, is contacted with a gelling agent for a period of time from about a second to about 24 hours, preferably from about 1 minute to about 12 hours, more preferably from about 10 minutes to about 10 hours, and most preferably from about 30 minutes to about 8 hours.

**[0090]** In an embodiment, the ratio of the weight of the gelling agent to the weight of the transition metal of the catalyst compound is in the range of from about 0.01 to about 1000, preferably in the range of from 1 to about 100, more preferably in the range of from about 2 to about 50, and most preferably in the range of from 4 to about 20. In one embodiment, the ratio of the weight of the gelling agent to the weight of the transition metal of the catalyst compound is in the range of from about 2 to about 20,

more preferably in the range of from about 2 to about 12, and most preferably in the range of from 4 to about 10.

**[0091]** In another embodiment of the method of the invention, the weight percent of the gelling agent based on the total weight of the polymerization catalyst is in the range of from about 0.5 weight percent to about 500 weight percent, preferably in the range of from 1 weight percent to about 25 weight percent, more preferably in the range of from about 2 weight percent to about 12 weight percent, and most preferably in the range of from about 2 weight percent to about 10 weight percent. In another embodiment, the weight percent of the gelling agent based on the total weight of the polymerization catalyst is in the range of from 1 to about 50 weight percent, preferably in the range of from 2 weight percent to about 30 weight percent, and most preferably in the range of from about 2 weight percent to about 20 weight percent.

**[0092]** In an embodiment of the method of the invention, a supported conventional-type transition metal catalyst, preferably a supported bulky ligand metallocene catalyst, is tumbled with a gelling agent for a period of time such that a substantial portion of the supported catalyst is intimately mixed and/or substantially contacted with the gelling agent.

**[0093]** In a preferred embodiment of the invention the catalyst system of the invention is supported on a carrier, preferably the supported catalyst system is substantially dried, preformed, substantially dry and/or free flowing. In an especially preferred method of the invention, the preformed supported catalyst system is contacted with at least one gelling agent. The gelling agent may be in solution or slurry or in a dry state, preferably the gelling agent is in a substantially dry or dried state. In the most preferred embodiment, the gelling agent is contacted with a supported catalyst system, preferably a supported bulky ligand metallocene catalyst system in a rotary mixer under a nitrogen atmosphere, most preferably the mixer is a tumble mixer, or in a fluidized bed mixing process, in which the polymerization catalyst and the gelling agent are in a solid state, that is they are both substantially in a dry state or in a dried state.

**[0094]** In an embodiment of the method of the invention, a conventional-type transition metal catalyst compound, preferably a bulky ligand metallocene catalyst compound, is contacted with a carrier to form a supported catalyst compound. In this method, an activator or a cocatalyst for the catalyst compound is contacted with a separate carrier to form a supported activator or supported cocatalyst. It is contemplated in this particular embodiment of the invention, that a gelling agent is then mixed with the supported catalyst compound or the supported activator or cocatalyst, in any order, separately mixed, simultaneously mixed, or mixed with only one of the supported

catalyst, or preferably the supported activator prior to mixing the separately supported catalyst and activator or cocatalyst.

**[0095]** In an embodiment, the method of the invention provides for co-injecting an unsupported polymerization catalyst and a gelling agent into the reactor. In one embodiment the polymerization catalyst is used in an unsupported form, preferably in a liquid form such as described in U.S. Patent Nos. 5,317,036 and 5,693,727 and European publication EP-A-0 593 083, all of which are herein incorporated by reference. The polymerization catalyst in liquid form can be fed with a gelling agent to a reactor using the injection methods described in PCT publication WO 97/46599, which is fully incorporated herein by reference.

**[0096]** Where a gelling agent and an unsupported bulky ligand metallocene catalyst system combination is utilized, the mole ratio of the metal of the activator component to the metal of the bulky ligand metallocene catalyst compound is in the range of between 0.3:1 to 10,000:1, preferably 100:1 to 5000:1, and most preferably 500:1 to 2000:1.

### **Polymerization Process**

**[0097]** The supported catalyst systems and/or compositions of the invention described above are suitable for use in any prepolymerization and/or polymerization process over a wide range of temperatures and pressures. The temperatures may be in the range of from -60 °C to about 280°C, preferably from 50°C to about 200°C, and the pressures employed may be in the range from 1 atmosphere to about 500 atmospheres or higher.

**[0098]** Polymerization processes include solution, gas phase, slurry phase and a high pressure process or a combination thereof. Particularly preferred is a gas phase or slurry phase polymerization of one or more olefins at least one of which is ethylene or propylene.

**[0099]** In one embodiment, the process of this invention is directed toward a solution, high pressure, slurry or gas phase polymerization process of one or more olefin monomers having from 2 to 30 carbon atoms, preferably 2 to 12 carbon atoms, and more preferably 2 to 8 carbon atoms. The invention is particularly well suited to the polymerization of two or more olefin monomers of ethylene, propylene, butene-1, pentene-1, 4-methyl-pentene-1, hexene-1, octene-1 and decene-1.

**[0100]** Other monomers useful in the process of the invention include ethylenically unsaturated monomers, diolefins having 4 to 18 carbon atoms, conjugated or nonconjugated dienes, polyenes, vinyl monomers and cyclic olefins. Non-limiting monomers useful in the invention may include norbornene, norbornadiene, isobutylene,



isoprene, vinylbenzocyclobutane, styrenes, alkyl substituted styrene, ethylidene norbornene, dicyclopentadiene and cyclopentene.

**[0101]** In the most preferred embodiment of the process of the invention, a copolymer of ethylene is produced, where with ethylene, a comonomer having at least one alpha-olefin having from 4 to 15 carbon atoms, preferably from 4 to 12 carbon atoms, and most preferably from 4 to 8 carbon atoms, is polymerized in a gas phase process.

**[0102]** In another embodiment of the process of the invention, ethylene or propylene is polymerized with at least two different comonomers, optionally one of which may be a diene, to form a terpolymer.

**[0103]** In one embodiment, the invention is directed to a polymerization process, particularly a gas phase or slurry phase process, for polymerizing propylene alone or with one or more other monomers including ethylene, and/or other olefins having from 4 to 12 carbon atoms. Polypropylene polymers may be produced using the particularly bridged bulky ligand metallocene catalysts as described in U.S. Patent Nos. 5,296,434 and 5,278,264, both of which are herein incorporated by reference.

**[0104]** Typically in a gas phase polymerization process a continuous cycle is employed where in one part of the cycle of a reactor system, a cycling gas stream, otherwise known as a recycle stream or fluidizing medium, is heated in the reactor by the heat of polymerization. This heat is removed from the recycle composition in another part of the cycle by a cooling system external to the reactor. Generally, in a gas fluidized bed process for producing polymers, a gaseous stream containing one or more monomers is continuously cycled through a fluidized bed in the presence of a catalyst under reactive conditions. The gaseous stream is withdrawn from the fluidized bed and recycled back into the reactor. Simultaneously, polymer product is withdrawn from the reactor and fresh monomer is added to replace the polymerized monomer. See for example U.S. Patent Nos. 4,543,399; 4,588,790; 5,028,670; 5,317,036; 5,352,749; 5,405,922; 5,436,304; 5,453,471; 5,462,999; 5,616,661; and 5,668,228, all of which are fully incorporated herein by reference.

**[0105]** The reactor pressure in a gas phase process may vary from about 100 psig (690 kPa) to about 500 psig (3448 kPa), preferably in the range of from about 200 psig (1379 kPa) to about 400 psig (2759 kPa), more preferably in the range of from about 250 psig (1724 kPa) to about 350 psig (2414 kPa).

**[0106]** The reactor temperature in a gas phase process may vary from about 30°C to about 120°C, preferably from about 60°C to about 115°C, more preferably in the range of from about 70°C to 110°C, and most preferably in the range of from about 70°C to about 95°C.

**[0107]** Other gas phase processes contemplated by the process of the invention include series or multistage polymerization processes. Also gas phase processes contemplated by the invention include those described in U.S. Patent Nos. 5,627,242, 5,665,818 and 5,677,375, and European publications EP-A- 0 794 200 EP-B1-0 649 992, EP-A- 0 802 202 and EP-B- 634 421 all of which are herein fully incorporated by reference.

**[0108]** In a preferred embodiment, the reactor utilized in the present invention is capable and the process of the invention is producing greater than 500 lbs of polymer per hour (227 Kg/hr) to about 200,000 lbs/hr (90,900 Kg/hr) or higher of polymer, preferably greater than 1000 lbs/hr (455 Kg/hr), more preferably greater than 10,000 lbs/hr (4540 Kg/hr), even more preferably greater than 25,000 lbs/hr (11,300 Kg/hr), still more preferably greater than 35,000 lbs/hr (15,900 Kg/hr), still even more preferably greater than 50,000 lbs/hr (22,700 Kg/hr) and most preferably greater than 65,000 lbs/hr (29,000 Kg/hr) to greater than 100,000 lbs/hr (45,500 Kg/hr).

**[0109]** A slurry polymerization process generally uses pressures in the range of from about 1 to about 50 atmospheres and even greater and temperatures in the range of 0°C to about 120°C. In a slurry polymerization, a suspension of solid, particulate polymer is formed in a liquid polymerization diluent medium to which ethylene and comonomers and often hydrogen along with catalyst are added. The suspension including diluent is intermittently or continuously removed from the reactor where the volatile components are separated from the polymer and recycled, optionally after a distillation, to the reactor. The liquid diluent employed in the polymerization medium is typically an alkane having from 3 to 7 carbon atoms, preferably a branched alkane. The medium employed should be liquid under the conditions of polymerization and relatively inert. When a propane medium is used the process must be operated above the reaction diluent critical temperature and pressure. Preferably, a hexane or an isobutane medium is employed.

**[0110]** A preferred polymerization technique of the invention is referred to as a particle form polymerization, or a slurry process where the temperature is kept below the temperature at which the polymer goes into solution. Such technique is well known in the art, and described in for instance U.S. Patent No. 3,248,179, which is fully incorporated herein by reference. Other slurry processes include those employing a loop reactor and those utilizing a plurality of stirred reactors in series, parallel, or combinations thereof. Non-limiting examples of slurry processes include continuous loop or stirred tank processes. Also, other examples of slurry processes are described in U.S. Patent No. 4,613,484, which is herein fully incorporated by reference.

[0111] In an embodiment the reactor used in the slurry process of the invention is capable of and the process of the invention is producing greater than 2000 lbs of polymer per hour (907 Kg/hr), more preferably greater than 5000 lbs/hr (2268 Kg/hr), and most preferably greater than 10,000 lbs/hr (4540 Kg/hr). In another embodiment the slurry reactor used in the process of the invention is producing greater than 15,000 lbs of polymer per hour (6804 Kg/hr), preferably greater than 25,000 lbs/hr (11,340 Kg/hr) to about 100,000 lbs/hr (45,500 Kg/hr).

[0112] Examples of solution processes are described in U.S. Patent Nos. 4,271,060, 5,001,205, 5,236,998 and 5,589,555 and PCT WO 99/32525, which are fully incorporated herein by reference

[0113] A preferred process of the invention is where the process, preferably a slurry or gas phase process is operated in the presence of a bulky ligand metallocene catalyst system of the invention and in the absence of or essentially free of any scavengers, such as triethylaluminum, trimethylaluminum, tri-isobutylaluminum and tri-n-hexylaluminum and diethyl aluminum chloride, dibutyl zinc and the like. This preferred process is described in PCT publication WO 96/08520 and U.S. Patent No. 5,712,352 and 5,763,543, which are herein fully incorporated by reference.

#### **Polymer Products**

[0114] The polymers produced by the process of the invention can be used in a wide variety of products and end-use applications. The polymers produced by the process of the invention include linear low density polyethylene, elastomers, plastomers, high density polyethylenes, medium density polyethylenes, low density polyethylenes, polypropylene and polypropylene copolymers.

[0115] The polymers, typically ethylene based polymers, have a density in the range of from 0.86g/cc to 0.97 g/cc, preferably in the range of from 0.88 g/cc to 0.965 g/cc, more preferably in the range of from 0.900 g/cc to 0.96 g/cc, even more preferably in the range of from 0.905 g/cc to 0.95 g/cc, yet even more preferably in the range from 0.910 g/cc to 0.940 g/cc, and most preferably greater than 0.915 g/cc, preferably greater than 0.920 g/cc, and most preferably greater than 0.925 g/cc. Density is measured in accordance with ASTM-D-1238.

[0116] The polymers produced by the process of the invention typically have a molecular weight distribution, a weight average molecular weight to number average molecular weight ( $M_w/M_n$ ) of greater than 1.5 to about 15, particularly greater than 2 to about 10, more preferably greater than about 2.2 to less than about 8, and most preferably from 2.5 to 8.

**[0117]** Also, the polymers of the invention typically have a narrow composition distribution as measured by Composition Distribution Breadth Index (CDBI). Further details of determining the CDBI of a copolymer are known to those skilled in the art. See, for example, PCT Patent Application WO 93/03093, published February 18, 1993, which is fully incorporated herein by reference.

**[0118]** The bulky ligand metallocene catalyzed polymers of the invention in one embodiment have CDBI's generally in the range of greater than 50% to 100%, preferably 99%, preferably in the range of 55% to 85%, and more preferably 60% to 80%, even more preferably greater than 60%, still even more preferably greater than 65%.

**[0119]** In another embodiment, polymers produced using a bulky ligand metallocene catalyst system of the invention have a CDBI less than 50%, more preferably less than 40%, and most preferably less than 30%.

**[0120]** The polymers of the present invention in one embodiment have a melt index (MI) or ( $I_2$ ) as measured by ASTM-D-1238-E in the range from 0.01 dg/min to 1000 dg/min, more preferably from about 0.01 dg/min to about 100 dg/min, even more preferably from about 0.1 dg/min to about 50 dg/min, and most preferably from about 0.1 dg/min to about 10 dg/min.

**[0121]** The polymers of the invention in a specific embodiment have a melt index ratio ( $I_{21}/I_2$ ) ( $I_{21}$  is measured by ASTM-D-1238-F) of from 10 to less than 25, more preferably from about 15 to less than 25.

**[0122]** The polymers of the invention in a preferred embodiment have a melt index ratio ( $I_{21}/I_2$ ) ( $I_{21}$  is measured by ASTM-D-1238-F) of from preferably greater than 25, more preferably greater than 30, even more preferably greater than 40, still even more preferably greater than 50 and most preferably greater than 65. In an embodiment, the polymer of the invention may have a narrow molecular weight distribution and a broad composition distribution or vice-versa, and may be those polymers described in U.S. Patent No. 5,798,427 incorporated herein by reference.

**[0123]** In yet another embodiment, propylene based polymers are produced in the process of the invention. These polymers include atactic polypropylene, isotactic polypropylene, hemi-isotactic and syndiotactic polypropylene. Other propylene polymers include propylene block or impact copolymers. Propylene polymers of these types are well known in the art see for example U.S. Patent Nos. 4,794,096, 3,248,455, 4,376,851, 5,036,034 and 5,459,117, all of which are herein incorporated by reference.

**[0124]** The polymers of the invention may be blended and/or coextruded with any other polymer. Non-limiting examples of other polymers include linear low density polyethylenes produced via conventional Ziegler-Natta and/or bulky ligand metallocene

catalysis, elastomers, plastomers, high pressure low density polyethylene, high density polyethylenes, polypropylenes and the like.

**[0125]** Polymers produced by the process of the invention and blends thereof are useful in such forming operations as film, sheet, and fiber extrusion and co-extrusion as well as blow molding, injection molding and rotary molding. Films include blown or cast films formed by coextrusion or by lamination useful as shrink film, cling film, stretch film, sealing films, oriented films, snack packaging, heavy duty bags, grocery sacks, baked and frozen food packaging, medical packaging, industrial liners, membranes, etc. in food-contact and non-food contact applications. Fibers include melt spinning, solution spinning and melt blown fiber operations for use in woven or non-woven form to make filters, diaper fabrics, medical garments, geotextiles, etc. Extruded articles include medical tubing, wire and cable coatings, pipe, geomembranes, and pond liners. Molded articles include single and multi-layered constructions in the form of bottles, tanks, large hollow articles, rigid food containers and toys, etc.

### **EXAMPLES**

**[0126]** In order to provide a better understanding of the present invention, including representative advantages thereof, the following examples are offered.

#### **Example 1**

##### **Preparation of Catalyst A**

**[0127]** Into a 2 gal (7.57 liter) reactor was charged 1060g of a 30 wt% Methylalumoxane (MAO) solution in toluene available from Albemarle Corp, Baton Rouge LA, followed by 1.5 liters of toluene. While stirring 19.8 g of dimethylsilyl-bis(tetrahydroindenyl)zirconium dichloride, a bridged bulky ligand metallocene was added to the reactor as an 8 wt% toluene solution and the mixture was stirred for 60 min. at room temperature to form a pre-mixed catalyst solution. Silica dehydrated at 600°C available from Crosfield Limited, Warrington, England was then added slowly in one third increments to the pre-mixed solution in the reactor. The mixture was stirred at room temperature for 20 minutes after which 24 grams of Kemamine AS-990 (which has the formula of  $(C_{18}H_{37}NCH_2CH_2OH)_2$  and is available from Witco Corp., Memphis, Tennessee) was added to the reactor as a 10 wt% solution in toluene, and stirring continued for an additional 30 minutes at room temperature. The temperature was then raised to 68°C (155°F) and vacuum was applied in order to dry the polymerization catalyst. Drying was continued for about 6 hours at low agitation until the catalyst appeared to be free flowing. It was then discharged into a flask and stored under nitrogen

atmosphere. The yield was 1050 grams due to some losses during the drying process. Analysis of the catalyst yielded: Zr = 0.32 wt%, Al = 11.8 wt%.

### Comparative Example 2 (CEX 2)

#### 5 Polymerization Process

g 3/15/04  
[0128] A 2 liter autoclave reactor under a nitrogen purge was charged with 0.16 mmoles of triethylaluminum (TEAL) as a scavenger of impurities followed by 25 cubic centimeters ~~cubic centimeters~~ of hexene-1 comonomer and 800 cubic centimeters of isobutane diluent. The content of the reactor was heated to 80°C after which 100 mgs of the silica supported catalyst prepared as described in Example 1 (Catalyst A) mixed in 10 cubic centimeters of hexane was added to the reactor. The catalyst hexane mixture was introduced concurrently with ethylene into the reactor to make up a total reactor pressure of 325 psig (2240 kPa). The reactor temperature was maintained at 85°C and the polymerization was allowed to proceed for 40 minutes. After 40 minutes the reactor was cooled, ethylene was vented off and the reactor opened. The reactor walls and stirrer blades were observed for polymer deposits and depending on the extent of fouling material the catalyst was given a rating from 0 to 6; 0 meaning no fouling material was observed on the reactor walls or stirrer blades, and 6 meaning that all polymer granules or particles were deposited onto the walls of the reactor or stirrer (that is, there was no free flowing polymer particles).

### Example 2

[0129] Example 2 was carried out in a manner similar to comparative example 2 (CEX 2) with the following exception: Prior to adding catalyst A to the reactor, 1 mg (1 wt% based on the weight of the catalyst charged) of tetraoctadecyl ammonium bromide, an organic gelling agent was mixed with the 100 milligrams of catalyst A and the 10 cubic centimeters of hexane. The mixture was then introduced into the reactor concurrently with the ethylene and reaction proceeded as described in Comparative Example 2.

30 [0130] As shown in Table 1, the reactor fouled badly in the absence of the organogelator, while free flowing granules and no wall deposits were seen when the organogelator was present.

**Table1**

Example	Gelling Agent	Amount of Gelling Agent Used	Fouling Rating	Comments
CEX 2	None	0	4	Extensive polymer deposits on walls and stirrer
2	tetraoctadecyl ammonium bromide	1 mg	0	No wall or stirrer deposits/fouling

**5      Examples 3-6 and comparative examples 3-9**

**[0131]**      In another evaluation, several materials were investigated to determine whether they exhibited the characteristic of a gelling agent. The gelling agent characteristic was determined by dissolving 2 weight percent of each respective material in 50 ml of n-hexane at ambient or at 5°C increment up to 100°C with agitation. After dissolution, the mixture was allowed to stand at ambient (or cool to ambient) without agitation for 5 minutes and was immediately observed for gelation; that is, the various mixtures were visually inspected for the formation of a colloidal dispersion having a viscoelastic liquid-like or solid-like characteristic.

**[0132]**      After determining whether the various materials exhibited a gelling agent characteristic, the materials were then evaluated for their respective effects on reactor performance using the procedure described above for Example 2. In this evaluation, comparative example 2 was repeated and designated comparative example 3 (CEX 3). The results of the gelling agent determination and the reactor performance evaluation are shown below in Table 2.

**[0133]**      Table 2 indicates that some of the materials exhibited a gelling agent characteristic while others did not. Table 2 also indicates that some of the materials that did not exhibit a gelling agent characteristic (that is, "non-gelling materials"), nonetheless provided improved reactor fouling protection (see CEX 5 and 6) while other non-gelling materials did not provide substantially improved protection (see CEX 7-9).

But finally, as we surprisingly discovered, Table 2 further indicates that all of the materials that exhibited a gelling agent characteristic, consistently provided substantially improved reactor fouling protection (that is, the fouling rating was less than 2.0). Thus, to consistently ensure substantially improved reactor protection against fouling and/or sheeting, at least one gelling agent should be used in combination, in contact and/or in a mixture with the polymerization catalyst system. The gelling agent can be combined,

contacted or mixed with the polymerization catalyst system prior to or after introduction in to the reactor but preferably the combining, contacting and/or mixing occurs prior to induction in to the reactor.

**[0134]** While the present invention has been described and illustrated by

- 5 reference to particular embodiments, those of ordinary skill in the art will appreciate that the invention lends itself to variations not necessarily illustrated herein. For example, it is contemplated that a gelling agent can be added to reactor in addition to being contacted with the catalyst system of the invention. For this reason, then, reference should be made solely to the appended claims for purposes of determining the true scope of the present
- 10 invention.

11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80 81 82 83 84 85 86 87 88 89 90 91 92 93 94 95 96 97 98 99 100 101 102 103 104 105 106 107 108 109 110 111 112 113 114 115 116 117 118 119 120 121 122 123 124 125 126 127 128 129 130 131 132 133 134 135 136 137 138 139 140 141 142 143 144 145 146 147 148 149 150 151 152 153 154 155 156 157 158 159 160 161 162 163 164 165 166 167 168 169 170 171 172 173 174 175 176 177 178 179 180 181 182 183 184 185 186 187 188 189 190 191 192 193 194 195 196 197 198 199 200 201 202 203 204 205 206 207 208 209 210 211 212 213 214 215 216 217 218 219 220 221 222 223 224 225 226 227 228 229 230 231 232 233 234 235 236 237 238 239 240 241 242 243 244 245 246 247 248 249 250 251 252 253 254 255 256 257 258 259 260 261 262 263 264 265 266 267 268 269 270 271 272 273 274 275 276 277 278 279 280 281 282 283 284 285 286 287 288 289 290 291 292 293 294 295 296 297 298 299 300 301 302 303 304 305 306 307 308 309 310 311 312 313 314 315 316 317 318 319 320 321 322 323 324 325 326 327 328 329 330 331 332 333 334 335 336 337 338 339 340 341 342 343 344 345 346 347 348 349 350 351 352 353 354 355 356 357 358 359 360 361 362 363 364 365 366 367 368 369 370 371 372 373 374 375 376 377 378 379 380 381 382 383 384 385 386 387 388 389 390 391 392 393 394 395 396 397 398 399 400 401 402 403 404 405 406 407 408 409 410 411 412 413 414 415 416 417 418 419 420 421 422 423 424 425 426 427 428 429 430 431 432 433 434 435 436 437 438 439 440 441 442 443 444 445 446 447 448 449 450 451 452 453 454 455 456 457 458 459 460 461 462 463 464 465 466 467 468 469 470 471 472 473 474 475 476 477 478 479 480 481 482 483 484 485 486 487 488 489 490 491 492 493 494 495 496 497 498 499 500 501 502 503 504 505 506 507 508 509 510 511 512 513 514 515 516 517 518 519 520 521 522 523 524 525 526 527 528 529 530 531 532 533 534 535 536 537 538 539 540 541 542 543 544 545 546 547 548 549 550 551 552 553 554 555 556 557 558 559 560 561 562 563 564 565 566 567 568 569 570 571 572 573 574 575 576 577 578 579 580 581 582 583 584 585 586 587 588 589 590 591 592 593 594 595 596 597 598 599 600 601 602 603 604 605 606 607 608 609 610 611 612 613 614 615 616 617 618 619 620 621 622 623 624 625 626 627 628 629 630 631 632 633 634 635 636 637 638 639 640 641 642 643 644 645 646 647 648 649 650 651 652 653 654 655 656 657 658 659 660 661 662 663 664 665 666 667 668 669 670 671 672 673 674 675 676 677 678 679 680 681 682 683 684 685 686 687 688 689 690 691 692 693 694 695 696 697 698 699 700 701 702 703 704 705 706 707 708 709 710 711 712 713 714 715 716 717 718 719 720 721 722 723 724 725 726 727 728 729 730 731 732 733 734 735 736 737 738 739 740 741 742 743 744 745 746 747 748 749 750 751 752 753 754 755 756 757 758 759 760 761 762 763 764 765 766 767 768 769 770 771 772 773 774 775 776 777 778 779 780 781 782 783 784 785 786 787 788 789 790 791 792 793 794 795 796 797 798 799 800 801 802 803 804 805 806 807 808 809 810 811 812 813 814 815 816 817 818 819 820 821 822 823 824 825 826 827 828 829 830 831 832 833 834 835 836 837 838 839 840 841 842 843 844 845 846 847 848 849 850 851 852 853 854 855 856 857 858 859 860 861 862 863 864 865 866 867 868 869 870 871 872 873 874 875 876 877 878 879 880 881 882 883 884 885 886 887 888 889 890 891 892 893 894 895 896 897 898 899 900 901 902 903 904 905 906 907 908 909 910 911 912 913 914 915 916 917 918 919 920 921 922 923 924 925 926 927 928 929 930 931 932 933 934 935 936 937 938 939 940 941 942 943 944 945 946 947 948 949 950 951 952 953 954 955 956 957 958 959 960 961 962 963 964 965 966 967 968 969 970 971 972 973 974 975 976 977 978 979 980 981 982 983 984 985 986 987 988 989 990 991 992 993 994 995 996 997 998 999 1000 1001 1002 1003 1004 1005 1006 1007 1008 1009 1010 1011 1012 1013 1014 1015 1016 1017 1018 1019 1020 1021 1022 1023 1024 1025 1026 1027 1028 1029 1030 1031 1032 1033 1034 1035 1036 1037 1038 1039 1040 1041 1042 1043 1044 1045 1046 1047 1048 1049 1050 1051 1052 1053 1054 1055 1056 1057 1058 1059 1060 1061 1062 1063 1064 1065 1066 1067 1068 1069 1070 1071 1072 1073 1074 1075 1076 1077 1078 1079 1080 1081 1082 1083 1084 1085 1086 1087 1088 1089 1090 1091 1092 1093 1094 1095 1096 1097 1098 1099 1100 1101 1102 1103 1104 1105 1106 1107 1108 1109 1110 1111 1112 1113 1114 1115 1116 1117 1118 1119 1120 1121 1122 1123 1124 1125 1126 1127 1128 1129 1130 1131 1132 1133 1134 1135 1136 1137 1138 1139 1140 1141 1142 1143 1144 1145 1146 1147 1148 1149 1150 1151 1152 1153 1154 1155 1156 1157 1158 1159 1160 1161 1162 1163 1164 1165 1166 1167 1168 1169 1170 1171 1172 1173 1174 1175 1176 1177 1178 1179 1180 1181 1182 1183 1184 1185 1186 1187 1188 1189 1190 1191 1192 1193 1194 1195 1196 1197 1198 1199 1200 1201 1202 1203 1204 1205 1206 1207 1208 1209 1210 1211 1212 1213 1214 1215 1216 1217 1218 1219 1220 1221 1222 1223 1224 1225 1226 1227 1228 1229 1230 1231 1232 1233 1234 1235 1236 1237 1238 1239 1240 1241 1242 1243 1244 1245 1246 1247 1248 1249 1250 1251 1252 1253 1254 1255 1256 1257 1258 1259 1260 1261 1262 1263 1264 1265 1266 1267 1268 1269 1270 1271 1272 1273 1274 1275 1276 1277 1278 1279 1280 1281 1282 1283 1284 1285 1286 1287 1288 1289 1290 1291 1292 1293 1294 1295 1296 1297 1298 1299 1300 1301 1302 1303 1304 1305 1306 1307 1308 1309 1310 1311 1312 1313 1314 1315 1316 1317 1318 1319 1320 1321 1322 1323 1324 1325 1326 1327 1328 1329 1330 1331 1332 1333 1334 1335 1336 1337 1338 1339 1340 1341 1342 1343 1344 1345 1346 1347 1348 1349 1350 1351 1352 1353 1354 1355 1356 1357 1358 1359 1360 1361 1362 1363 1364 1365 1366 1367 1368 1369 1370 1371 1372 1373 1374 1375 1376 1377 1378 1379 1380 1381 1382 1383 1384 1385 1386 1387 1388 1389 1390 1391 1392 1393 1394 1395 1396 1397 1398 1399 1400 1401 1402 1403 1404 1405 1406 1407 1408 1409 1410 1411 1412 1413 1414 1415 1416 1417 1418 1419 1420 1421 1422 1423 1424 1425 1426 1427 1428 1429 1430 1431 1432 1433 1434 1435 1436 1437 1438 1439 1440 1441 1442 1443 1444 1445 1446 1447 1448 1449 1450 1451 1452 1453 1454 1455 1456 1457 1458 1459 1460 1461 1462 1463 1464 1465 1466 1467 1468 1469 1470 1471 1472 1473 1474 1475 1476 1477 1478 1479 1480 1481 1482 1483 1484 1485 1486 1487 1488 1489 1490 1491 1492 1493 1494 1495 1496 1497 1498 1499 1500 1501 1502 1503 1504 1505 1506 1507 1508 1509 1510 1511 1512 1513 1514 1515 1516 1517 1518 1519 1520 1521 1522 1523 1524 1525 1526 1527 1528 1529 1530 1531 1532 1533 1534 1535 1536 1537 1538 1539 1540 1541 1542 1543 1544 1545 1546 1547 1548 1549 1550 1551 1552 1553 1554 1555 1556 1557 1558 1559 1560 1561 1562 1563 1564 1565 1566 1567 1568 1569 1570 1571 1572 1573 1574 1575 1576 1577 1578 1579 1580 1581 1582 1583 1584 1585 1586 1587 1588 1589 1590 1591 1592 1593 1594 1595 1596 1597 1598 1599 1600 1601 1602 1603 1604 1605 1606 1607 1608 1609 1610 1611 1612 1613 1614 1615 1616 1617 1618 1619 1620 1621 1622 1623 1624 1625 1626 1627 1628 1629 1630 1631 1632 1633 1634 1635 1636 1637 1638 1639 1640 1641 1642 1643 1644 1645 1646 1647 1648 1649 1650 1651 1652 1653 1654 1655 1656 1657 1658 1659 1660 1661 1662 1663 1664 1665 1666 1667 1668 1669 1670 1671 1672 1673 1674 1675 1676 1677 1678 1679 1680 1681 1682 1683 1684 1685 1686 1687 1688 1689 1690 1691 1692 1693 1694 1695 1696 1697 1698 1699 1700 1701 1702 1703 1704 1705 1706 1707 1708 1709 1710 1711 1712 1713 1714 1715 1716 1717 1718 1719 1720 1721 1722 1723 1724 1725 1726 1727 1728 1729 1730 1731 1732 1733 1734 1735 1736 1737 1738 1739 1740 1741 1742 1743 1744 1745 1746 1747 1748 1749 1750 1751 1752 1753 1754 1755 1756 1757 1758 1759 1760 1761 1762 1763 1764 1765 1766 1767 1768 1769 1770 1771 1772 1773 1774 1775 1776 1777 1778 1779 1780 1781 1782 1783 1784 1785 1786 1787 1788 1789 1790 1791 1792 1793 1794 1795 1796 1797 1798 1799 1800 1801 1802 1803 1804 1805 1806 1807 1808 1809 1810 1811 1812 1813 1814 1815 1816 1817 1818 1819 1820 1821 1822 1823 1824 1825 1826 1827 1828 1829 1830 1831 1832 1833 1834 1835 1836 1837 1838 1839 1840 1841 1842 1843 1844 1845 1846 1847 1848 1849 1850 1851 1852 1853 1854 1855 1856 1857 1858 1859 1860 1861 1862 1863 1864 1865 1866 1867 1868 1869 1870 1871 1872 1873 1874 1875 1876 1877 1878 1879 1880 1881 1882 1883 1884 1885 1886 1887 1888 1889 1890 1891 1892 1893 1894 1895 1896 1897 1898 1899 1900 1901 1902 1903 1904 1905 1906 1907 1908 1909 1910 1911 1912 1913 1914 1915 1916 1917 1918 1919 1920 1921 1922 1923 1924 1925 1926 1927 1928 1929 1930 1931 1932 1933 1934 1935 1936 1937 1938 1939 1940 1941 1942 1943 1944 1945 1946 1947 1948 1949 1950 1951 1952 1953 1954 1955 1956 1957 1958 1959 1960 1961 1962 1963 1964 1965 1966 1967 1968 1969 1970 1971 1972 1973 1974 1975 1976 1977 1978 1979 1980 1981 1982 1983 1984 1985 1986 1987 1988 1989 1990 1991 1992 1993 1994 1995 1996 1997 1998 1999 2000 2001 2002 2003 2004 2005 2006 2007 2008 2009 2010 2011 2012 2013 2014 2015 2016 2017 2018 2019 2020 2021 2022 2023 2024 2025 2026 2027 2028 2029 2030 2031 2032 2033 2034 2035 2036 2037 2038 2039 2040 2041 2042 2043 2044 2045 2046 2047 2048 2049 2050 2051 2052 2053 2054 2055 2056 2057 2058 2059 2060 2061 2062 2063 2064 2065 2066 2067 2068 2069 2070 2071 2072 2073 2074 2075 2076 2077 2078 2079 2080 2081 2082 2083 2084 2085 2086 2087 2088 2089 2090 2091 2092 2093 2094 2095 2096 2097 2098 2099 2100 2101 2102 2103 2104 2105 2106 2107 2108 2109 2110 2111 2112 2113 2114 2115 2116 2117 2118 2119 2120 2121 2122 2123 2124 2125 2126 2127 2128 2129 2130 2131 2132 2133 2134 2135 2136 2137 2138 2139 2140 2141 2142 2143 2144 2145 2146 2147 2148 2149 2150 2151 2152 2153 2154 2155 2156 2157 2158 2159 2160 2161 2162 2163 2164 2165 2166 2167 2168 2169 2170 2171 2172 2173 2174 2175 2176 2177 2178 2179 2180 2181 2182 2183 2184 2185 2186 2187 2188 2189 2190 2191 2192 2193 2194 2195 2196 2197 2198 2199 2200 2201 2202 2203 2204 2205 2206 2207 2208 2209 2210 2211 2212 2213 2214 2215 2216 2217 2218 2219 2220 2221 2222 2223 2224 2225 2226 2227 2228 2229 2230 2231 2232 2233 2234 2235 2236 2237 2238 2239 2240 2241 2242 2243 2244 2245 2246 2247 2248 2249 2250 2251 2252 2253 2254 2255 2256 2257 2258 2259 2260 2261 2262 2263 2264 2265 2266 2267 2268 2269 2270 2271 2272 2273 2274 2275 2276 2277 2278 2279 2280 2281 2282 2283 2284 2285 2286 2287 2288 2289 2290 2291 2292 2293 2294 2295 2296 2297 2298 2299 2300 2301 2302 2303 2304 2305 2306 2307 2308 2309 2310 2311 2312 2313 2314 2315 2316 2317 2318 2319 2320 2321 2322 2323 2324 2325 2326 2327 2328 2329 2330 2331 2332 2333 2334 2335 2336 2337 2338 2339 2340 2341 2342 2343 2344 2345 2346 2347 2348 2349 2350 2351 2352 2353 2354 2355 2356 2357 2358 2359 2360 2361 2362 2363 2364 2365 2366 2367 2368 2369 2370 2371 2372 2373 2374 2375 2376 2377 2378 2379 2380 2381 2382 2383 2384 2385 2386 2387 2388 2389 2390 2391 2392 2393 2394 2395 2396 2397 2398 2399 2400 2401 2402 2403 2404 2405 2406 2407 2408 2409 2410 2411 2412 2413 2414 2415 2416 2417 2418 2419 2420 2421 2422 2423 2424 2425 2426 2427 2428 2429 2430 2431 2432 2433 2434 2435 2436 2437 2438 2439 2440 2441 2442 2443 2444 2445 2446 2447 2448 2449 2450 2451 2452 2453 2454 2455 2456 2457 2458 2459 2460 2461 2462 2463 2464 2465 2466 2467 2468 2469 2470 2471 2472 2473 2474 2475 2476 2477 2478 2479 2480 2481 2482 2483 2484 2485 2486 2487 2488 2489 2490 2491 2492 2493 2494 2495 2496 2497 2498 2499 2500 2501 2502 2503 2504 2505 2506 2507 2508 2509 2510 2511 2512 2513 2514 2515 2516 2517 2518 2519 2520 2521 2522 2523 2524 2525 2526 2527 2528 2529 2530 2531 2532 2533 2534 2535 2536 2537 2538 2539 2540 2541 2542 2543 2544 2545 2546 2547 2548 2549 2550 2551 2552 2553 2554 2555 2556 2557 2558 2559 2560 2561 2562 2563 2564 2565 2566 2567 2568 2569 2570 2571 2572 2573 2574 2575 2576 2577 2578 2579 2580 2581 2582 2583 2584 2585 2586 2587 2588 2589 2590 2591 2592 2593 2594 2595 2596 2597 2598 2599 2600 2601 2602 2603 2604 2605 2606 2607 2608 2609 2610 2611 2612 2613 2614 2615 2616 2617 2618 2619 2620 2621 2622 2623 2624 2625 2626 2627 2628 2629 2630 2631 2632 2633 2634 2635 2636 2637 2



Table 2

Examples	Materials	Gelling Agent Characteristic	Reactor Fouling Protection	Fouling Rating
CEX 3	None	NA	NA	5
EX 3	(OH)Al(ROPOR') <sub>2</sub>	Yes	Yes	0.5
EX 4	(Et)Al(ROPOR') <sub>2</sub>	Yes	Yes	1
EX 5	(Et)Al(ROPOR) <sub>2</sub>	Yes	Yes	0.25
EX 6	Mg(ROPOR') <sub>2</sub>	Yes	Yes	0.25
CEX 4	ROPOR'	No	No	3
CEX 5	(Bu)Mg(ROPOR')	No	Yes	0.5
CEX 6	(Et) <sub>2</sub> Al(ROPOR')	No	Yes	0.5
CEX 7	Zn(ROPOR') <sub>2</sub>	No	No	2.5
CEX 8	(Et)Zn(ROPOR')	No	No	2
CEX 9	Product of Fe <sub>3</sub> O <sub>4</sub> + ROPOR'	No, only thickening	No	2.5

NA denotes not applicable.